

Best Available Copy

PATENT

Atty. Dkt. No. QLYM/0085

IN THE CLAIMS:

Please amend the claims as follows:

1. (Previously Presented) A laser level assembly, comprising:
 - a base having a laser coupled thereto;
 - at least one attachment means for attaching the laser level to a surface, the attachment means selected from at least one member of the group consisting of a suction assembly, an anchoring assembly, a magnet, and an adhesive;
 - an adjustment assembly, wherein the adjustment assembly provides a micro adjustment of at least a portion of the laser level relative to the surface;
 - an auxiliary base attachable to the base to provide leveling adjustments; and
 - a lens assembly movable between at least two positions, wherein each position of the lens assembly selectively aligns and positions a different one of at least two lenses with respect to the laser.
2. (Previously Presented) A laser level assembly, comprising:
 - a base;
 - a laser; and
 - a suction assembly to provide a suction between the suction assembly and a surface, the suction for attaching the laser level assembly to the surface, wherein the suction assembly comprises:
 - a pad;
 - a yoke operatively connected to the pad; and
 - a lever extending to the yoke and shaped to raise the yoke when moved from a first position to a second position.
3. (Canceled)
4. (Previously Presented) The laser level assembly of claim 2, wherein the pad comprises a lip surrounding a periphery of the pad for contact with the surface.

Page 2

377697_1.DOC

PATENT

Any. Dkt. No. OLYM0096

5. (Previously Presented) The laser level assembly of claim 2, wherein an outer periphery wall of the base and at least one inner wall of the base located a distance from the outer periphery wall press against the pad to provide a seal between the surface and the pad.
6. (Previously Presented) The laser level assembly of claim 2, further comprising a magnet operatively connected to the yoke.
7. (Original) The laser level assembly of claim 2, further comprising an adapter unit for use with an adhesive to attach the laser level to the surface.
8. (Original) The laser level assembly of claim 2, further comprising a 45 degree vial.
9. (Original) The laser level assembly of claim 2, further comprising a belt clip.
10. (Previously Presented) A laser level assembly, comprising:
 - a base;
 - a structural member pivotally secured to the base;
 - a laser secured to the structural member; and
 - an adjustment assembly, wherein the adjustment assembly comprises a scotch yoke and provides a movement of the structural member relative to the base that is less than a movement applied to the adjustment assembly.
11. (Canceled)
12. (Original) The laser level assembly of claim 10, further comprising a 45 degree vial.
13. (Original) The laser level assembly of claim 10, further comprising a belt clip.

PATENT

Atty. Dkt. No. QLYM/0085

14. (Previously Presented) A laser level assembly, comprising:
a base;
a laser; and
a lens assembly, wherein the lens assembly is rotatable to selectively align and position one of at least two lenses with respect to the laser, the lens assembly comprising:
a rotary part that secures the at least two lenses on a plane in a circular arrangement; and
a detent mechanism, wherein a ball of the detent mechanism urges into a profile on an outside circumference of the rotary part.
15. (Original) The laser level assembly of claim 14, wherein the lens assembly comprises at least three lenses.
- 16-18. (Canceled)
19. (Previously Presented) The laser level assembly of claim 14, wherein the rotary part comprises a polygonal shaped center aperture with a member at least partially therein to attach the rotary part to the laser level assembly.
20. (Original) The laser level assembly of claim 14, further comprising a 45 degree vial.
21. (Original) The laser level assembly of claim 14, further comprising a belt clip.
- 22-32. (Canceled)
33. (Original) A laser level assembly, comprising:
a laser lever;
an auxiliary base comprising:

PATENT

Atty. Dkt. No. OLYM/0095

an upper plate;
a lower plate;
at least one elastomer connected to each plate; and
two screws at a first end of the auxiliary base that extend through the upper plate and contact the lower plate to provide leveling adjustments.

34. (Original) The laser level assembly of claim 33, further comprising a ball positioned within a socket defined by an area between the upper and lower plates at a second end of the auxiliary base.

35. (Original) A method for projecting a reference line on an object, comprising:
contacting a suction assembly of a laser level to a surface;
rotating a lever of the suction assembly to raise a portion of a pad thereby creating a suction between the pad and the surface; and
projecting a laser on the object to display the reference line.

36. (Original) The method of claim 35, further comprising:
rotating a rotary part to select a lens.

37. (Original) The method of claim 35, further comprising:
rotating an adjustment handle to provide micro adjustments of the laser level relative to the surface.

38. (Currently Amended) A method for projecting a reference line on an object, comprising:
attaching a laser level to a surface;
rotating an adjustment handle to provide micro adjustments of the laser level relative to the surface, wherein rotating the adjustment handle operates a scotch yoke of the laser level and rotates a portion of the laser level within a plane of the surface;
and

Page 5

377697_1.DOC

Best Available Copy

PATENT
Atty. Dkt. No. OLYM/0085

projecting a laser on the object to display the reference line.

39. (Canceled)

40. (Previously Presented) The method of claim 38, wherein the surface is a substantially vertical surface.

41. (Canceled)